



BONDING GUTTERS®

30 YEAR GUARANTEE

The GRP Bonding Gutters® create a weather-tight joint between dissimilar roof coverings on semi-detached and terrace homes whether it be new build or refurbishment. Available in two dry fix options and one for traditional mortar bedding.



FEATURES AND BENEFITS

- The flat and narrow profiles minimise the disturbance to adjoining roof
- Robust weather protection design with twin water bars on each side
- The dry fix options provide a neat finish to the edges of different roof coverings that may be at different heights
- Dry fix products eliminate the mortar installation and maintenance issues
- Up to half the cost and time of traditional lead
- Light in weight and easy to handle
- UV Resistant
- No harmful run-off or staining

APPLICATION

The Bonding Gutters® should be placed to allow the slate or tile bond to be maintained and using either a replacement tile and a half or wider slate if possible. Designed to fix directly over the tiling or slating battens.

When joining lengths, use the minimum lengths of overlap as follows:

ROOF PITCH	OVER 39°	30° - 39°	22.5° - 29°	BELOW 22.5°
OVERLAP	150mm	200mm	300mm	350mm

Minimum roof pitch 17.5°.

PRODUCT CODES, DIMENSIONS AND COMPATIBILITY



Product code: HDL DBG1
Central Upstand: 70mm
Dimensions: W 210 x L 3000mm

To suit slates, flat interlocking and plain tiles.



Product code: HDL DBG2
Central Upstand: 100mm
Dimensions: W 210 x L 3000mm

To suit profiled tiles on one or both sides and also typical Scottish practice.




Product code: HDL BG
Dimensions: W 225 x L 3000mm

Traditional option with integral mortar bonding strip, suitable for all applications

MATERIAL AND COLOUR

GRP and Anthracite

RELATED PRODUCTS



Dry Fix GRP Valley Troughs

Provides a secure and discreet drainage for inclined roof valleys. Mortarless application and available in three profiles, codes: HDL DVT, DVLPT, DVS



CON6+ Universal Ridge and Hip System

Includes a ventilated membrane with broad corrugated adhesive strips, uni-ridge gaskets, stainless steel straps and fixing screws, code: HD CON6



Tile & Slate Breathable Roofing Underlays

Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180