



# CON6+ DRY RIDGE AND HIP SYSTEM

## 15 YEAR GUARANTEE

CON6+ is a universal ventilated dry fix ridge and hip system that can be used with all the commonly available ridge and hip tile types. CON6+ can be fitted to all roof pitches\* with no special tools required. The single unique universal jointing gasket adds flexibility and allows compatibility with the most commonly available ridge and hip tile profiles, including baby ridges.

### FEATURES AND BENEFITS

- Unique flexible and trimmable patented gasket features weatherproof, continuous integrated water channels and self-sealing detail for the stainless steel fixing screws
- Broader corrugations of the roll membrane edge compliment a variety of ridge tile designs and different roof pitches
- Suitable for ridge and hip tile applications
- Wider butyl strip provides improved and secure adhesion
- Stainless steel batten straps included
- Dry fix products eliminate the mortar installation and maintenance issues

### PACK CONTENTS

1 x 320mm x 6m Rollflex, 13 x universal gaskets, 13 x fixing plates, 13 x 100mm screws, 10 x ridge straps



\* Subject to being used in conjunction with ridge tiles suitable for that pitch

### PRODUCT CODE

HD CON6

### TECHNICAL INFORMATION

- Provides compliance with BS 5250 and BS 5534
- Minimum 5,000mm<sup>2</sup> airflow area per linear metre installed (actual 11,700mm<sup>2</sup>)
- Suitable for warm and cold roof applications
- Complies with BS 8612

COMPONENT	MATERIAL SPECIFICATION
Ridge Fixing Plate	High impact polyamide
Uni-Ridge Tile Gasket	LDPE
Ridge Batten Strap	Stainless Steel
Ridge Screw	Stainless Steel
Rollflex Ridge Roll	Polypropylene fabric with corrugated aluminium edges

### RELATED PRODUCTS

	<b>Tile Clip</b> For small interlocking tile cuts on hips and in valleys, code: HD DVC
	<b>Hip Tile Support Trays (optional)</b> 1.65m length, code HDL HT165 3m length, code: HDL HT300
	<b>Tile &amp; Slate Breathable Roofing Underlays</b> Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180