



# DRY FIX CONTINUOUS VERGES FOR SLATE

## 30 YEAR GUARANTEE

The continuous verge range are made up of preformed GRP continuous profiles designed to be used with natural or man-made slates. Designed to fix continuously along the verge with under batten fixing for new projects and face fixing for refurbishment work.





### FEATURES AND BENEFITS

- Quick and simple to install
- Thermally stable
- UV and acid rain resistant
- Lead alternative
- Reduced theft risk
- Creates no harmful run off into water courses
- Dry fix products eliminate the mortar installation and maintenance issues

### MATERIAL AND COLOUR

GRP and Anthracite

### TYPICAL DRY VERGE JOINT DETAILS

 <p><b>RIDGE JOINT</b></p>	<p><b>Ridges.</b> The Dry Verges are cut with a vertical mitre and butt jointed. A lead saddle may be fitted under or over the joint if required. The ridge tile should be trimmed if necessary to suit.</p>
 <p><b>VERGE JOINT</b></p>	<p><b>Verge.</b> Where joints in the dry verge are required along the edge of the roof, they should be overlapped with the lower section fitted over/around the upper section</p>
 <p><b>SPROCKET JOINT FIG.1</b></p>	<p><b>Sprockets.</b> Slight or gentle sprockets can easily be accommodated by cutting the lower section to a slight rake and fitting over the upper or main dry verge section</p>
 <p><b>SPROCKET JOINT FIG.2</b></p>	<p>These jointing methods are suitable for all of the dry verge profiles.</p>

### PRODUCT CODES AND SUITABILITY



**Product code: HDL DV6**  
**Slate gap: 40mm**  
**Length: 3000mm**  
 Designed to fit underneath the slating battens. Suitable for slate roofs both new and refurbishment work.



**Product code: HDL DV7**  
**Slate gap: 16mm**  
**Length: 3000mm**  
 Designed to fit underneath the roofing underlay and directly on top of the sark boarding in a typical Scottish roof detail.



**Product code: HDL DV8**  
**Slate gap: 55mm**  
**Length: 3000mm**  
 Designed primarily for face fixing as a refurbishment system but can be used on new build if required.




**Product code: HDL DV9**  
**Slate gap: 35mm**  
**Length: 3000mm**  
 Designed primarily as a refurbishment system but can be used on new build if required and where the slates are fixed directly to the sark board roof in typical Scottish slating practice.

### RELATED PRODUCTS



**CON6+ Universal Ridge & Hip System**  
 Includes a ventilated membrane with broad corrugated adhesive strips, patented gaskets, stainless steel straps and fixing screws, code: HD CON6



**Open Valley Troughs**  
 Three different profiles for slate and Scottish slate roofs, manufactured from GRP in Anthracite colour, codes: HDL SVTU, SVT, SSVT



**Slate Vent Range**  
 Manufactured from polypropylene, suitable for batten or sark board fixing, codes: HD SRV5U, SRV10U, SRV10/20, SRV680, ILSRV10/20, ILSRV10/24, ILSRV10/U