



EAVES AND SOFFIT VENTS

20 YEAR GUARANTEE

The eaves and soffit vent product range provides roofspace ventilation at the lowest level of the roofline.

FEATURES AND BENEFITS

- All grille and mesh sizes are designed in accordance BS 5250
- Soffit vents permit entry of air into the roofspace for most eaves details
- When soffit vents are fitted on opposite sides of a rectangular roof structure they will satisfy the requirements of the Building Regulations
- Vents designed help to avoid excessive airflow resistance and prevent the ingress of birds and large insects

PRODUCTS



Code: HD 8000
Airflow: 10,000mm² per m
Length: 2400mm
Colours: White and Brown
 Lightweight and easy to handle. Will support soffit boards between 4mm and 10mm in thickness and up to 300mm wide without additional noggins. For roof pitches above 15°.



Code: HD 8210
Airflow: 10,000mm² per m
Length: 2400mm
Colours: White and Brown
 To be used where the soffit board is fixed directly to the underside of the rafters. It can be used in no fascia situations, or at high level on a mono pitch roof. For roof pitches above 15°.



Code: HD 8310
Airflow: 10,000mm² per m
Length: 2400mm
Colour: Black
 Provides air ventilation at eaves level where a continuous masonry corbel of brick, or stone is constructed. Security wall ties can be attached at any position if required.



Code: HD 12000M
Airflow: 10,000mm² per m
Code: HD 12000U
Airflow: 10,000mm² or 25,000mm² per m
Colour: Black
 These vents provide a through-flow of ventilating air over the fascia board for both new build and refurbishment.



Code: HD 7000
Airflow: 2,500mm² each
Colours: White, Brown, Light Oak and Black
 These vents, when introduced into existing unventilated soffit boards, will permit entry of air into the roof-space.



RELATED PRODUCTS



3 in 1 Eaves Ventilation Pack
 A eaves to eaves ventilation system that includes an Over Fascia Vent (HD 12000M), Universal Roll Vent (HD 5000) and roofing Underlay Support Tray (HD 3000)



CON6+ Universal Ridge and Hip System
 Includes a ventilated membrane with broad corrugated adhesive strips, patented gaskets, stainless steel straps and fixing screws, code: HD CON6



Tile & Slate Breathable Roofing Underlays
 Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180