



- 1. Dryseal flat sheet: HDL H 1250F
- 2. Anti-corrosive fixings where required
- 3. Dryseal trim: HDL H 0200 A
- 4. Insulation
- 5. Insulation fillet (laminated in-situ between levels)
- 6. Substrate
- 7. Vapour control layer
- 8. Timber batten (Treated)
- 9. Adhesive button

Note: In-situ laminate over fixings and seams/joints omitted for clarity. Please see drawing no: JFD for more detail.

| | | |
|--|------------|----------|
| DRAWING TITLE | | |
| Through Wall Outlet to Hopper | | |
| PROJECT | | |
| NA | | |
| CLIENT | | |
| HDL | | |
| DRAWN | DATE | SHEET |
| DB | 12.10.2015 | 01 |
| SCALE | PAPER SIZE | REVISION |
| NTS | A4 | NA |
| DRAWING NO | | |
| WALLHOPP | | |
| Hambleside Danelaw Ltd | | |
| T 01327 701900 | | |
| F 01327 701909 | | |
| www.hambleside-danelaw.co.uk | | |
| - All dimensions are in millimetres unless otherwise stated | | |
| - All dimensions to be checked on site | | |
| - Do not scale | | |
| © Hambleside Danelaw Ltd, own the copyright of this document which is supplied in confidence, this document must not be used for any other purpose other than that it is supplied for. | | |

